

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Peter SATTLER et al.

Serial No. (unknown)

Filed herewith

ACTUATING CYLINDER FOR A
VALVE GATED INJECTION
MOULDING DEVICE

PRELIMINARY AMENDMENT

Commissioner of Patents

Washington, D.C. 20231

Sir:

Prior to calculation of the filing fee, please amend
the above-identified application as follows:

IN THE CLAIMS:

Amend claim 4 as follows:

--4. (amended) Injection moulding device (1)
according to claim 2, wherein the valve pin head (37) compris-
es a flat section which is received in the slot (36) in a
fixed angular position.

Amend claim 5 as follows:

--5. (amended) Injection moulding device (1)
according to claim 1, wherein the height adjustment means (40)
comprises a number of engagement elements (44) around its
perimeter, the cylinder housing (30) comprising an opening
(43) connecting with the engagement elements (44).

Amend claim 6 as follows:

20043301000

Peter SATTLER et al.

--6. (amended) Injection moulding device (1) according to claim 1, wherein the base member (14) comprises a cooling plate, having a cooling channel (18) located below the cylinder (15).

Add the following new claim:

--9. (new) Injection moulding device (1) according to claim 3, wherein the valve pin head (37) comprises a flat section which is received in the slot (36) in a fixed angular position.


R E M A R K S

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE".

Respectfully submitted,

YOUNG & THOMPSON

By


Benoît Castel
Attorney for Applicants
Registration No. 35,041
745 South 23rd Street
Arlington, VA 22202
Telephone: 703/521-2297

January 10, 2002

VERSION WITH MARKINGS TO SHOW CHANGES MADE

4. Injection moulding device (1) according to claim 2, ~~3 or 4~~, wherein the valve pin head (37) comprises a flat section which is received in the slot (36) in a fixed angular position.

5. Injection moulding device (1) according to ~~any~~ ~~of the preceding claims~~ claim 1, wherein the height adjustment means (40) comprises a number of engagement elements (44) around its perimeter, the cylinder housing (30) comprising an opening (43) connecting with the engagement elements (44).

6. Injection moulding device (1) according to ~~any~~ ~~of the preceding claims~~ claim 1, wherein the base member (14) comprises a cooling plate, having a cooling channel (18) located below the cylinder (15).

2004.03.04.001